

Tile Series Button Panel 2.0 (Plastic/metal version)

Product name	Buttons	Model No.
Tile Series Button Panel 2.0 (Plastic & metal versions)	1 Button Panel A	HDL-MP1B/TILE.48
	1 Button Panel B	HDL-MP2S/TILE.48
	2 Buttons Panel A	HDL-MP2B/TILE.48
	2 Buttons Panel B	HDL-MP4S/TILE.48
	4 Buttons Panel A	HDL-MP4B/TILE.48
	4 Buttons Panel B	HDL-MP4B-A/TILE.48
	Frames	HDL-MP1-EC/TILE.48

buspro

Datasheet

Issued: May 24, 2021

File Edition: E



Figure 1. 1 Button Panel A



Figure 2. 1 Button Panel B



Figure 3. 2 Buttons Panel A



Figure 4. 2 Buttons Panel B



Figure 5. 4 Buttons Panel A



Figure 6. 4 Buttons Panel B




Figure 6-1. 1 Button Panel A/1 Button Panel B






Figure 6-2. 4 Buttons Panel A/ 4 Buttons Panel B



2 Buttons Panel A/2 Buttons Panel B

Figure 7. Dimensions - Plastic version



2 Buttons Panel A/2 Buttons Panel B

Figure 8. Dimensions - Metal version



Figure 9. Dimensions - Side View




Figure 10. Components - Back View

Overview

Tile series Button Panel 2.0 (See Figure 1-6) contains 1/2/4-button panels, both plastic and metal versions. Icons and text of each button supports laser labelling. With built-in RGB backlight for each pushbutton, the color and brightness level can be set by HDL Buspro Setup Tool or manually set on the panel. The panels support controls of lighting, curtains, scenes, music, etc.

Functions

- Built-in temperature sensor
- Built-in proximity sensor
- Icons and text of each button support laser labelling.
- Adjustable backlight brightness level via HDL Buspro Setup Tool or manual setting on the panel
- Button modes: Single on/off, Single on, Single off, Combination on, Combination off, Combination on/off, Double click/single on/off, Double click/combination on/off, Momentary, Short/long press, Short press/long momentary.
- Control types: Scene, Sequence, Timer Switch, Universal Switch, Single Channel Lighting Control, Broadcast Scene, Broadcast Channel, Curtain Switch, GPRS Control, Panel Control, Security Module, Music Control, General Control, etc.
- Button lock function.
- Online update via HDL Buspro Setup Tool.

Important Notes

- Two buttons can be combined into one; for instance, A1 & A5 or A2 & A6 in Figure 6-2.
- The panel should be mounted on the wall box with power interface.
- It is recommended to connect wires in hand-in-hand.
- It is recommended to use dedicated HDL Buspro cable.

Product Information

1 Button Panel A/1 Button Panel B - See Figure 6-1

4 Buttons Panel A/4 Buttons Panel B - See Figure 6-2

Dimensions - See Figure 7 - 9

Components - See Figure 10

- 1. Button:** Control targets.
- 2. RGB backlight:** Color and brightness level can be set.
- 3. Icons & text:** Support laser labelling.
- 4. HDL Buspro bus connector**

Lock/Unlock panel: Short press button A1 and A4 (see Figure 6-1, 6-2, 7 and 8) simultaneously to lock/unlock the panel.

Backlight color setting: Press button A2 and A3 (see Figure 6-1, 6-2, 7 and 8) simultaneously for 5 seconds, and the panel enters color selecting mode. Pressing button A2 mean selecting previous color from local color library, while pressing button A3 means selecting next color. The color will be finally determined if no operation is done within 20 seconds.

Programming mode: Press Button A3 (HDL-MP1B/TILE.48, HDL-MP2S/TILE.48, MP2B/TILE.48, MP4S/TILE.48) for 3 seconds, all backlights turn red and the panel enters programming mode. Press any button (HDL-MP4B/TILE.48, MP4B-A/TILE.48) for 15 seconds until all backlights flash and turn blue, and the panel enters programming mode.

Upgrade mode: Press Buttons (HDL-MP1B/TILE.48, HDL-MP2S/TILE.48, MP2B/TILE.48, MP4S/TILE.48: Button A3 and A4; HDL-MP4B/TILE.48, MP4B-A/TILE.48: Button A2 and A3) simultaneously before powered on, release the buttons after being powered on for 3 seconds, then the panel enters upgrade mode.

Safety Precautions

- The installation and testing for the product must be carried out by HDL Automation Co., Ltd. or its appointed service agencies. The electric construction shall comply with local laws and safety regulations.
- The device should be wall box mounted. HDL will not be responsible for any consequence caused by the inexpert or faulty installation and wiring methods, which are not in accordance with the instructions contained in this operating instruction.
- Please do not privately disassemble or replace any parts of the product. Otherwise, it may cause mechanical fault, electric shock, fire or personal injuries.
- Please contact our after-sales departments or our designated service agencies for your maintenance service. Product failures caused by private disassembly are not subject to this warranty.

Package Contents

Panel*1 / Datasheet*1

Technical Data

Basic Parameters

Working voltage	12~30V DC
Working current	HDL-MP1B/TILE.48: 9.5mA/24V DC HDL-MP2S/TILE.48: 13.4mA/24V DC HDL-MP2B/TILE.48: 13.4mA/24V DC HDL-MP4S/TILE.48: 13.5mA/24V DC HDL-MP4B/TILE.48: 13.5mA/24V DC HDL-MP4B-A/TILE.48: 13.5mA/24V DC
Communication	HDL Buspro
Cable diameter of Buspro terminal	0.6-0.8mm

External Environment

Working temperature	-5°C~45°C
Working relative humidity	≤90%
Storage temperature	-20°C~60°C
Storage relative humidity	≤93%

Specifications

Dimensions	Plastic version: 86×86×11(mm) Metal version: 90×90×11(mm)
Net weight	Plastic version: 64g Metal version: 110g
Housing material	Plastic version: Flame retardant PC Metal version: Aluminum alloy
Installation	Wall box (See Figure 11)
Protection rating (Compliant with EN 60529)	IP20

Approved

CE

RoHS

HDL Buspro Cable Guide

HDL Buspro	HDL Buspro Cable
DATA+	Yellow
DATA-	White
COM	Black
24V DC	Red

Installation

Product installation

(Take HDL- MP4B/TILE.48 as an example)

Installation - See Figure 11

- Step ①: Install the wall box in the wall.
Step ②: Secure the power interface to the wall box with screws.
Step ③: Install the panel on the power interface.
Step ④: Install the frame around the panel.

Horizontal installation - See Figure 12

Vertical installation - See Figure 13




Figure 11. Installation




Figure 12. Horizontal installation

Figure 13. Vertical installation

Notes: Metal panels can be installed either horizontally or vertically.
Plastic panels can be only installed horizontally.

Product name	Frame Types	Gang	Dimensions
2/3/4-gang frames	Metal	2 gang	176*90*11(mm)
		3 gang	262*90*11(mm)
		4 gang	348*90*11(mm)
	Plastic	2 gang	172*86*11(mm)
		3 gang	258*86*11(mm)
		4 gang	344*86*11(mm)

Technical support

E-mail: hdltickets@hdlautomation.com

Website: <https://www.hdlautomation.com>

©Copyright by HDL Automation Co., Ltd. All rights reserved.
Specifications subject to change without notice.